

File/File H System - Reglette LED  
24W/m

code R18FM0.840D



**PRODUCT DESCRIPTION**

Modular system for direct, diffused and/or accent lighting, consisting of hollow profiles made from 66x40 mm painted or anodised extruded aluminium, with a predefined length or cut to measure, available in the following versions: wall-mounted, ceiling-mounted, suspended, recessed with a super-slim edge trim, just 5 mm wide (61.5 x 40 mm) and trimless recessed. To be integrated with LED linear light sources, battens for T16 fluorescent lamps, projectors with built-in LED source and max 16A 3-circuit track modules for inclusion of projectors. Fluorescent battens, complete with 50/60 Hz 230/240 V electronic power supply, LED batten driver included. To be completed with side end caps with Light Proof system, opal white or microprismatic PC diffusing screen (in accordance with EN 12464-1), closing profiles, with a predefined length or cut to measure, or dark-light aluminium grille with high specular qualities and mounting brackets or suspension cables. IP40 protection rating.

**PRODUCT SPECS**

Installation method	system
Light source	Led-en
Absorbed power	12,8 W
Color temperature	4000K
Color rendering index CRI	>90
Luminaire luminous flux	2044 lm
Luminous efficiency	160 lm/W
MacAdam color tolerance	3
Durata media stimata	50000h Ta 25° L70B10
Protocol	Dimmable
Voltage	230 V
Energy efficiency class	E
Dimension	L560 mm
IP Grade	IP20
Protection Class	Class I appliance

**WEB PAGE**



**ASSEMBLY INSTRUCTIONS**

