



Faretèn Minispot S for File system

code FR023.940F/01







TECHNICAL SHEET 15.05.2024



PRODUCT DESCRIPTION

Super compact accent lighting. Projectors programme featured by very contained dimensions, for use both in aluminum profiles, to mix accent with diffused lighting, and surface-mounted. The range articulates in two fixture types: spherical LED spot, adjustable on both vertical and horizontal axis, housed inside a five-units module, complete with driver and cylindrical LED projector, of 36 and 50 mm. diameter, adjustable on both vertical and horizontal axis, housed inside a one-or two-units module.

PRODUCT SPECS

Installation method	system
Light source	Led
Absorbed power	5x1,5 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Flood 28°
Finishing	Bianco
Luminaire luminous flux	700 lm
Luminous efficiency	93 lm/W
Power supply/transformer	Included
Protocol	On/Off
Energy efficiency class	E
Weight	0.40 Kg
Dimension	L300Wx38 Ø15 mm
IP Grade	IP20

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 1

LUCIFERO'S SRL with sole shareholder - via del Tappezziere, 3 - 40138 Bologna - Italy - +39 051 6014276 - assistenza@luciferos.it - customercare@luciferos.it