lucifero's
ARCHI-TECH LIGHTING

Faretèn focus 55S, for File system
code FR042.930F/01

E | IP20 | A | ⏚ | ⚠ | LED incl | UKCA | CE

PRODUCT DESCRIPTION

Modular system for direct, diffused and/or accent lighting, consisting of hollow profiles made from 66x40 mm painted or anodised extruded aluminium, with a predefined length or cut to measure, available in the following versions: wall-mounted, ceiling-mounted, suspended ,recessed with a super-slim edge trim, just 5 mm wide (61.5 x 40 mm) and trimless recessed. To be integrated with LED linear light sources, battens for T16 fluorescent lamps, projectors with built-in LED source and max 16A 3-circuit track modules for inclusion of projectors. Fluorescent battens, complete with 50/60 Hz 230/240 V electronic power supply, LED batten driver included. To be completed with side end caps with Light Proof system, opal white or microprismatic PC diffusing screen (in accordance with EN 12464-1), closing profiles, with a predefined length or cut to measure, or dark-light aluminium grille with high specular qualities and mounting brackets or suspension cables. IP40 protection rating.

PRODUCT SPECS

Installation method	system
Light source	Led
Absorbed power	12 W
Color temperature	3000K
Color rendering index CRI	>90
Optic	Flood
Finishing	White
Luminaire luminous flux	1350 lm
Luminous efficiency	113 lm/W
MacAdam color tolerance	2
Durata media stimata	2SDCM 50000h L90 B10 ta 25°C
Power supply/transformer	Included
Protocol	On/Off
Energy efficiency class	E
Weight	0.63 Kg
Dimension	L300Wx38Hx115 Ø55 mm
IP Grade	IP20
Protection Class	Class I appliance

LENS 50 LED   **27°**

cd/klm

615
1230
1845
2460

η = 100 %

300 | 60 | Ø55 | 38

WEB PAGE

ASSEMBLY INSTRUCTIONS

Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.
Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.
We reserve the right to make changes to our products at any time.

LUCIFERO'S SRL with sole shareholder - via del Tappezziere, 3 - 40138 Bologna - Italy - +39 051 6014276 - assistenza@luciferos.it -
customercare@luciferos.it

OPTIONAL ACCESSORIES

Accessori Lens With Ring Asymmetric lens with ring ø55

code L055A.A

uncategorized. White finishing
Warning: Not suitable with halogen lamp

Technical Sheet

code L055A.A

uncategorized. Black finishing
Warning: Not suitable with halogen lamp

Technical Sheet

Accessori Lens With Ring Elipsoid lens with ring ø55

code L055E.A

uncategorized. White finishing
Warning: Not suitable with halogen lamp

Technical Sheet

code L055E.A

uncategorized. Black finishing
Warning: Not suitable with halogen lamp

Technical Sheet

Accessori Lens With Ring Honeycomb louver with ring ø55

code L055R.A

uncategorized. White finishing

Technical Sheet

Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.
Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.
We reserve the right to make changes to our products at any time.

code L055R.A

uncategorized. Black finishing

Accessori Lens With Ring Satin lens with rings ø55

code L055S.A

uncategorized. White finishing
Warning: Not suitable with halogen lamp

Technical Sheet

code L055S.A

uncategorized. Black finishing
Warning: Not suitable with halogen lamp

Technical Sheet