

Minifile Ceiling LED 3000K

code ML208.830/01




PRODUCT DESCRIPTION

ceiling lamp LED with opaline diffuser

PRODUCT SPECS

| | |
|------------------------------|-------------------------|
| Installation method | Ceiling surface mounted |
| Light source | Led-en |
| Absorbed power | 64 W |
| Color temperature | 3000K |
| Color rendering index CRI | >80 |
| Finishing | Bianco |
| Luminous flux of the product | 3606 lm |
| Luminous efficiency | 56 lm/W |
| MacAdam color tolerance | 3 |
| Durata media stimata | 50000h Ta 25° L70B10 |
| Power supply/transformer | Included |
| Protocol | On/Off |
| Energy efficiency class | E |
| Dimension | L2825 mm |
| IP Grade | IP40 |
| Protection Class | Class I appliance |



WEB PAGE



ASSEMBLY INSTRUCTIONS



OPTIONAL ACCESSORIES

Accessori Wallbox Couple of closure heads for wallbox MINIFILE

code LTM200.1



Modular system for direct, diffused, accent or wallwasher, made of 62x32 mm painted or anodised extruded aluminium empty profiles, available in predefined lengths or cut to measure. Available in wall-mounted, ceiling-mounted, suspended, trimless recessed or recessed with super-slim 5 mm. width edge trim versions. To be integrated with linear LED sources, LED spotlights, complete with 50/60 Hz 230/240 V electronic power supply. To be completed with Light Proof system side end caps, opal white polycarbonate diffusing screen, quick mounting extruded aluminium shapers (for linear LEDs and spotlight LEDs) or closing profiles, available in predefined lengths or cut to measure, and mounting brackets or suspension cables. IP20 or IP40 protection degree depending on the selected lighting combinations.

Technical Sheet

