Guide System Spot focus 55 LED
code GU003.940F/01

| E | 500 | 500 | 350 | 350 | IP20 | III | A |

LED incl. | UKCA | CE

PRODUCT DESCRIPTION

Cylindrical projector in extruded aluminium, adjustable on the vertical axis of 355, and on the horizontal axis of +/- 90, equipped with hook for installation on the profile; powder coating; with COB technology (Chip on Board) for maximum efficiency; absence of multiple shadows; Energy efficient LEDs with high color rendering; secondary lens in high transparency pmma; optical units available as accessories with replacement without tools; available accessories such as honey comb, elipsoid lens, asymmetric lens, satined lens. Color finish bianco.

PRODUCT SPECS

Installation method	system
Light source	Led
Absorbed power	12 W / 18 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Flood 27°
Finishing	Bianco
Luminous flux of the product	1400 lm / 1750 lm
Luminous efficiency	117 lm/W / 97 lm/W
MacAdam color tolerance	2
Durata media stimata	2SDCM 50000h L90 B10 ta 25°C / 50000h Ta 25° L70B10
Power supply/transformer	Not included
Protocol	See power supply
Energy efficiency class	E
Dimension	H125 Ø55 mm
IP Grade	IP20
Protection Class	Class III appliance
gruppi alimentatori	500mA
gruppi alimentatori	500mA

Ø 55

LENS 50 LED 27°

cd/klm

615
1230
1845
2460

η = 100 %

WEB PAGE

ASSEMBLY INSTRUCTIONS

OPTIONAL ACCESSORIES

Accessori Lens With Ring Asymmetric lens with ring ø55

code L055A.A

uncategorized. White finishing
Warning: Not suitable with halogen lamp

code L055A.A

uncategorized. Black finishing
Warning: Not suitable with halogen lamp

Accessori Lens With Ring Elipsoid lens with ring ø55

code L055E.A

uncategorized. White finishing
Warning: Not suitable with halogen lamp

code L055E.A

uncategorized. Black finishing
Warning: Not suitable with halogen lamp

Accessori Lens With Ring Honeycomb louver with ring ø55

code L055R.A

uncategorized. White finishing

Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.
Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.
We reserve the right to make changes to our products at any time.

Page 2 / 3

code L055R.A

uncategorized. Black finishing

Accessori Lens With Ring Satin lens with rings ø55

code L055S.A

uncategorized. White finishing
Warning: Not suitable with halogen lamp

code L055S.A

uncategorized. Black finishing
Warning: Not suitable with halogen lamp