

## Recessed Minifile profile with Leva modules

code ML022.940W/01




### PRODUCT DESCRIPTION

Direct light recessed lamp with 5-light Leva modules.

### PRODUCT SPECS

|                              |                         |
|------------------------------|-------------------------|
| Installation method          | recessed                |
| Light source                 | LED                     |
| Absorbed power               | 10x2,2 W                |
| Color temperature            | 4000K                   |
| Color rendering index CRI    | >90                     |
| Optic                        | Wide 50°                |
| Finishing                    | White box - black optic |
| Luminous flux of the product | 1694 lm                 |
| Luminous efficiency          | 77 lm/W                 |
| MacAdam color tolerance      | 2                       |
| Life time estimate           | 50000h Ta 25° L90B10    |
| Protocol                     | On/Off                  |
| Energy efficiency class      | E                       |
| Weight                       | 1.60 Kg                 |
| Dimension                    | L1140 mm                |
| Hole size                    | 42xL+2 mm               |
| IP Grade                     | IP20                    |



### WEB PAGE



### ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

Page 1 / 1