

Mini Sight Minimal 3M

code MS70.935F/01




PRODUCT DESCRIPTION

Square recessed fixture without frame, 3 lamps. Adjustable pull-out optic

PRODUCT SPECS

Installation method	Trimless recessed
Light source	LED
Absorbed power	3x12 W / 3x18 W
Color temperature	3500K
Color rendering index CRI	>90
Optic	Flood 27°
Finishing	White
Luminous flux of the product	4050 lm / 4797 lm
Luminous efficiency	113 lm/W / 89 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Energy efficiency class	D
Weight	1.50 Kg
Dimension	L288xW96xH135 Ø55 mm
IP Grade	IP20
Protection Class	Class III appliance



WEB PAGE




ASSEMBLY INSTRUCTIONS



MANDATORY ACCESSORIES

Box mini sight 3M

code MSC13




Galvanized metal wallbox to be recessed in brick walls or reinforced concrete to fit the article MINI sight 3M

Technical Sheet



Accessori Wallbox Frame for Mini sight 3M

code MSC23



inspectable Frame to Be Fixed and plastered in 15mm height plasterBoard False ceilings

Technical Sheet



