

Mini Sight Minimal 4M

code MS80.940W/01





















Square recessed fixture without frame, 4 lamps. Adjustable pull-out optic

PRODUCT SPECS

Installation method	Trimless recessed
Light source	Led
Absorbed power	4x12 W / 4x18 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Wide 46°
Finishing	White
Luminaire luminous flux	5347 lm / 6699 lm
Luminous efficiency	111 lm/W / 93 lm/W
MacAdam color tolerance	2
Durata media stimata	2SDCM 50000h L90 B10 ta 25°C / 50000h Ta 25° L70B10
Power supply/transformer	Not included
Protocol	See power supply
Energy efficiency class	E
Weight	1.85 Kg
Dimension	L193Wx193Hx135 Ø55 mm
Hole size	squared cut vedi accessori mm
IP Grade	IP20
Protection Class	Class III appliance







WEB PAGE








Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

MANDATORY ACCESSORIES

Accessori Wallbox Frame for Mini sight 4M




code MSC24

inspectaBle Frame to Be Fixed and plastered in 15mm height plasterBoard False ceilings



Accessori Wallbox Wallbox mini sight 4M



code MSC14

Galvanized metal wallbox to be recessed in brick walls or reinforced concrete to fit the article MINI INCAS $4\mathrm{M}$



