

Mini Sight Minimal 4M

code MS80.927W/01



350



















PRODUCT DESCRIPTION

Square recessed fixture without frame, 4 lamps. Adjustable pull-out optic

PRODUCT SPECS

Installation method	Trimless recessed
Light source	LED
Absorbed power	4x12 W / 4x18 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Wide 46°
Finishing	White
Luminous flux of the product	5060 lm / 6076 lm
Luminous efficiency	105 lm/W / 84 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Energy efficiency class	D
Weight	1.85 Kg
Dimension	L193xW193xH135 Ø55 mm
Dimension Hole size	
	mm
Hole size	mm vedi accessori mm
Hole size IP Grade	mm vedi accessori mm IP20
Hole size IP Grade Protection Class	mm vedi accessori mm IP20 Class III appliance





WEB PAGE








Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

MANDATORY ACCESSORIES

Accessori Wallbox Frame for Mini sight 4M


code MSC24



inspectaBle Frame to Be Fixed and plastered in 15mm height plasterBoard False ceilings

Technical Sheet

Box mini sight 4M



code MSC14

Galvanized metal wallbox to be recessed in brick walls or reinforced concrete to fit the article MINI INCAS 4M



