

Microfile H Exagonal Suspension biemission

code MFH061.840/01






















PRODUCT DESCRIPTION

Suspended, recessed, wall/ceiling lighting fixtures in extruded aluminum for direct or bi-emission diffused lighting of circular, square, rectangular or hexagonal shape complete with silicone screen. Integrated linear LED sources to be completed with 24Vdc remote power supply. IP44. Available default modules on demand and modular system.

PRODUCT SPECS

Installation method	Suspension
Light source	Linea Led
Absorbed power	2x102 W
Color temperature	4000K
Color rendering index CRI	>80
Finishing	White
Luminous flux of the product	9586 lm
Luminous efficiency	47 lm/W
Protocol	On/Off
Energy efficiency class	D
Dimension	L1541xW1335 mm
IP Grade	lp44
Protection Class	Class III appliance
Power supply/Transformer	Not included
Protocol	See power supply





WEB PAGE



ASSEMBLY



OPTIONAL ACCESSORIES

Lbs System Canopy for housing driver



code LB421/01

REGISTERED DESIGN - File Flex is a versatile extruded aluminium profile, which can design infinite shapes. Its asymmetrical section is designed to realize unique lighting effects meanwhile ensuring optimal illumination levels. The linear LED source screened by a flexible opal extruded silicone diffuser creates seamless lighting effects. The system allows the use of blind modules, multi-optic from Leva series or adjustable spot from Spot Focus series Ø26 and Ø36. It has to be completed by stabilized drivers 24V or 48V.



Lbs System Canopy for plasterboard false-ceiling

Lbs System Canopy for plasterboard false-ceiling



code LB428/01

Lbs System Canopy for plasterboard false-ceiling



Accessori Joints for Microfile H exagonal

code MFH080

uncategorized

code MFH081

uncategorized



Technical Sheet

