




Leva Quadra Recessed Q9

code LV411.940F/01





LED				32°
105°	\sim	ad //dm	X	105°
90°		cd/klm		90°
75°				759
60°		1500		60°
45°		2000		45°
		2500		
		3000	η = ·	100 %
30°	15°	0°	15°	30°

PRODUCT DESCRIPTION

700

Е

Fix and adjustable projectors family with chip on board LED sources. Mounting options: recessed, with frame or trimless, ceiling and wall-mounted and on 48V tracks, such as the Multi System by Stucchi. Fixture's body in painted extruded aluminum. Optical group complete with CRI>90 chip on board led, lens, antiglare housing and electronic driver (except for recessed versions). The optical group is fixed in the recessed version and adjustable (0-90° on the horizontal axis and 355° on the vertical axis) in the surfacemounted and track versions. Spot, flood and wide optics. UGR<19. Degree of protection IP20/40.

A 📼 🖉 🚸 ۲۲ 🖽 🧲

PRODUCT SPECS

Installation method	Recessed with frame, Ceiling surface mounted	
Light source	LED	
Absorbed power	9x2,2 W	
Color temperature	4000K	
Color rendering index CRI	>90	
Optic	Flood 32°	
Finishing	White box - black optic	
Luminous flux of the product	1714 lm	
Luminous efficiency	87 lm/W	
MacAdam color tolerance	2	
Life time estimate	50000h Ta 25° L90B10	
Energy efficiency class	E	
Weight	0.90 Kg	
Dimension	L98xW98xH115 mm	
Hole size	80 mm mm	
IP Grade	IP20	
Protection Class	Class III appliance	
Power supply/Transformer	Not included	
Protocol	See power supply	

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 1

LUCIFERO'S SRL with sole shareholder - via del Tappezziere, 3 - 40138 Bologna - Italy - +39 051 6014276 - assistenza@luciferos.it - customercare@luciferos.it