

## Ceiling Minifile profile with Leva modules

code ML223.930S/01



### PRODUCT DESCRIPTION

Linear light module with direct emission. 40x66mm section aluminum extrusion profile. Equipped with 2 LEVA series groups of 5 spots with high color rendering LED sources and mounted on a linear aluminum dissipator; fixed optics with available apertures 20° - 32° - 50° - 41°x18°. The structural composition of the optical system determines a controlled glare emission (UGR 16). Partial blind screens in extruded aluminum arranged for combination with end caps on both sides. Electronic control gear integrated in the luminaire. Optional version with DALI dimming. Type of ceiling installation.

### PRODUCT SPECS

|                              |                         |
|------------------------------|-------------------------|
| Installation method          | Ceiling surface mounted |
| Light source                 | LED                     |
| Absorbed power               | 10x2,2 W                |
| Color temperature            | 3000K                   |
| Color rendering index CRI    | >90                     |
| Optic                        | Spot 20°                |
| Finishing                    | White box - black optic |
| Luminous flux of the product | 2004 lm                 |
| Luminous efficiency          | 91 lm/W                 |
| MacAdam color tolerance      | 2                       |
| Life time estimate           | 50000h Ta 25° L90B10    |
| Protocol                     | On/Off                  |
| Energy efficiency class      | E                       |
| Weight                       | 2.20 Kg                 |
| Dimension                    | L1420 mm                |
| IP Grade                     | IP20                    |
| Power supply                 | 220-240V 50-60Hz        |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS

