



Semplice Wall/ceiling Projector P55

code SE504.930F/01



















PRODUCT DESCRIPTION

Luminaire for interiors direct projection light, with adjustable optics. Optical unit made in extruded aluminum rotatable 180 degrees on the horizontal axis. The friction hinge system bound to the base allows easy rotation/adjustment in all direction with an anti rotational locking system of 355° along the vertical axis.

PRODUCT SPECS

Light source Led-en	
Absorbed power 18 W	
Color temperature 3000K	
Color rendering index CRI >90	
Optic Flood 27°	
Finishing White	
Luminaire luminous flux 1575 lm	
Luminous efficiency 87 lm/W	
MacAdam color tolerance 2	
Durata media stimata 50000h Ta 25° L	70B10
Power supply/transformer Included	
Protocol On/Off	
Energy efficiency class E	
Weight 1.0 Kg	
Dimension H200 Ø55 mm	
IP Grade IP20	

WEB PAGE







OPTIONAL ACCESSORIES

Accessori Lens With Ring Asymmetric lens with ring ø55



code L055A.A

uncategorized. White finishing Warning: Not suitable with halogen lamp



code L055A.A



uncategorized. Black finishing Warning: Not suitable with halogen lamp



Accessori Lens With Ring Elipsoid lens with ring ø55



code L055E.A

uncategorized. White finishing Warning: Not suitable with halogen lamp




code L055E.A



uncategorized. Black finishing Warning: Not suitable with halogen lamp



Accessori Lens With Ring Honeycomb louver with ring ø55



code L055R.A

uncategorized. White finishing





code L055R.A

uncategorized. Black finishing



Accessori Lens With Ring Satin lens with rings ø55



code L055S.A

uncategorized. White finishing Warning: Not suitable with halogen lamp



code L055S.A



uncategorized. Black finishing Warning: Not suitable with halogen lamp



