

**Pro Edge system - Spot Focus 90**

code PE203.930W/01

**PRODUCT DESCRIPTION**

Cylindrical projector in extruded aluminium, adjustable on the vertical axis of 355, and on the horizontal axis of +/- 90, equipped with hook for installation on the profile; powder coating; with COB technology (Chip on Board) for maximum efficiency; absence of multiple shadows; Energy efficient LEDs with high color rendering; secondary lens in high transparency pmma; precise photometric curve with different emission angles; optical units available as accessories with replacement without tools; hot plug protection; available accessories such as honey comb, ellipsoid lens, asymmetric lens, satined lens. Color finish white.

**PRODUCT SPECS**

|                              |                                 |
|------------------------------|---------------------------------|
| Installation method          | system                          |
| Light source                 | LED                             |
| Absorbed power               | 17 W / 24,3 W                   |
| Color temperature            | 3000K                           |
| Color rendering index CRI    | >90                             |
| Optic                        | Wide 38°                        |
| Finishing                    | White                           |
| Luminous flux of the product | 2227 lm / 3183 lm               |
| Luminous efficiency          | 131 lm/W                        |
| MacAdam color tolerance      | 3                               |
| Life time estimate           | 3SDCM 50000h L90 B10<br>ta 25°C |
| Energy efficiency class      | D / E                           |
| Dimension                    | H110 Ø90 mm                     |

**WEB PAGE****ASSEMBLY  
INSTRUCTIONS**