

## Pro Edge system - Spot Focus 90

code PE203.940F/01



### PRODUCT DESCRIPTION

Cylindrical projector in extruded aluminium, adjustable on the vertical axis of 355, and on the horizontal axis of +/- 90, equipped with hook for installation on the profile; powder coating; with COB technology (Chip on Board) for maximum efficiency; absence of multiple shadows; Energy efficient LEDs with high color rendering; secondary lens in high transparency pmma; precise photometric curve with different emission angles; optical units available as accessories with replacement without tools; hot plug protection; available accessories such as honey comb, ellipsoid lens, asymmetric lens, satined lens. Color finish white.

### PRODUCT SPECS

|                              |                              |
|------------------------------|------------------------------|
| Installation method          | system                       |
| Light source                 | LED                          |
| Absorbed power               | 17 W / 24,3 W                |
| Color temperature            | 4000K                        |
| Color rendering index CRI    | >90                          |
| Optic                        | Flood 24°                    |
| Finishing                    | White                        |
| Luminous flux of the product | 2261 lm / 3230 lm            |
| Luminous efficiency          | 133 lm/W                     |
| MacAdam color tolerance      | 3                            |
| Life time estimate           | 3SDCM 50000h L90 B10 ta 25°C |
| Energy efficiency class      | D / E                        |
| Dimension                    | H110 Ø90 mm                  |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS

