

Pro Edge system - Spot Focus 90

code PE204.9HCW/01

**PRODUCT DESCRIPTION**

Cylindrical projector in extruded aluminium, adjustable on the vertical axis of 355, and on the horizontal axis of +/- 90, equipped with hook for installation on the profile; powder coating; with COB technology (Chip on Board) for maximum efficiency; absence of multiple shadows; Energy efficient LEDs with high color rendering; secondary lens in high transparency pmma; precise photometric curve with different emission angles; optical units available as accessories with replacement without tools; hot plug protection; available accessories such as honey comb, ellipsoid lens, asymmetric lens, satined lens. Color finish white.

PRODUCT SPECS

Installation method	system
Light source	LED
Absorbed power	32 W
Color temperature	Horticulture
Color rendering index CRI	>90
Optic	Wide 38°
Finishing	White
MacAdam color tolerance	3
Life time estimate	50000h Ta 25° L80B10
Energy efficiency class	E
Dimension	H110 Ø90 mm

WEB PAGE**ASSEMBLY INSTRUCTIONS**

Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

Page 1 / 1