

Focus Mini Track T36 trimless back recessed

code FS502A.935F/01





















166 Ø36



PRODUCT DESCRIPTION

Cylindrical projector in extruded aluminum for installation on Mini Track System, electrified track in very low voltage; installation and positioning by means of quick-coupling insertion tools free; adjustable on the vertical axis of 355 and on the horizontal axis of +/- 90; powder coating or galvanic treatment; with COB (Chip on Board) technology for maximum efficiency; absence of multiple shadows; energy efficient LEDs with high color rendering; on-board electronic converter with Dali2 DT8 2-channel protocol; rear optical group; secondary lens in high transparency pmma; optical units available as accessories with replacement without tools; hot plug protection and power supply without respect for polarity; available accessories such as honey comb, elipsoid lens, asymmetric lens, satined lens. Color finish white.

PRODUCT SPECS

Light source LED Absorbed power 8 W Color temperature 3500K Color rendering index CRI >90
Color temperature 3500K
Color rendering index CRI >90
Color rendering index Orti >50
Optic Flood 28°
Finishing White
Luminous flux of the product 560 lm
Luminous efficiency 70 lm/W
MacAdam color tolerance 3
Life time estimate 3SDCM 50000h L90 B1 Ta 25°C
Protocol On/Off
Energy efficiency class E
Dimension W166 Ø36 mm
IP Grade IP20
Power supply/Transformer Not included
Protocol See power supply

WEB PAGE



ASSEMBLY



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.