

# File Flex Outdoor Circle Floor T800

code FXG02.830/01






TECHNICAL SHEET 13.05.2024


## PRODUCT DESCRIPTION

Family of outdoor lighting fixtures - floor, wall, ceiling or suspended –realized by extruded aluminum profiles with curvilinear shapes. Versions with LED linear source with extruded opal flexible silicone screen for diffused light and versions with multi-optic LED modules of the Leva series for accent lighting are available. IP66.

## PRODUCT SPECS

Installation method	Floor
Light source	Linear-led-18w-mt-168-led-mt-1590- mt-ip65
Absorbed power	44 W
Color temperature	3000K
Finishing	White
Luminaire luminous flux	3874 lm
Luminous efficiency	88 lm/W
Protocol	On/Off
Voltage	24 V
Weight	4.3 Kg
Dimension	H834 Ø800 mm
Protection Class	Class III appliance
Product Spec	Circular shape





### WEB PAGE



#### ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 2

LUCIFERO'S SRL with sole shareholder - via del Tappezziere, 3 - 40138 Bologna - Italy - +39 051 6014276 - assistenza@luciferos.it - customercare@luciferos.it

