

## Iferrosi Floor POLE H3500-60+60

code IF04.940F/99


















# 350° 350° 350° 350° 350° 350° 350° 350°



### PRODUCT DESCRIPTION

Family of outdoor floor or wall luminaires, available in finished modules or in a modular system for maximum customization. Versions with LED source for accent light are available. Poles of different heights from 700mm to 3000mm are available, to be combined with spots of 6.7W or 18W. Fixing base or possibility to install in different surfaces: flange for wooden surfaces, clamp for concrete and stake for ground. IP54.

# **PRODUCT SPECS**

Installation method	Floor
Light source	Led
Absorbed power	2x6,7 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Flood 24°
Finishing	Grafite
Luminous flux of the product	834 lm
Luminous efficiency	62 lm/W
MacAdam color tolerance	3
Power supply/transformer	Not included
Protocol	See power supply
Energy efficiency class	D
Weight	16 Kg
Dimension	L450x800Hx3500 mm
IP Grade	lp66
Protection Class	Class III appliance

## **WEB PAGE**







### **OPTIONAL ACCESSORIES**

# Lbs System Box for power suppliers



### code IF76

Family of outdoor floor or wall luminaires, available in in a modular system for maximum customization. Versions with LED source for accent light are available. Poles of different heights from 700mm to 3000mm are available, to be combined with spots of 6.7W or 18W. Fixing base or possibility to install in different surfaces: flange for wooden surfaces, clamp for concrete and stake for ground. IP54.

