


Iferrosi Floor POLE H700-36

code IF06.940F/62









PRODUCT DESCRIPTION

Family of outdoor floor or wall luminaires, available in finished modules or in a modular system for maximum customization. Versions with LED source for accent light are available. Poles of different heights from 700mm to 3000mm are available, to be combined with spots of 6.7W or 18W. Fixing base or possibility to install in different surfaces: flange for wooden surfaces, clamp for concrete and stake for ground. IP54.

PRODUCT SPECS

Light sourceLedAbsorbed power8 WColor temperature4000K	
Color temperature 4000K	
Color rendering index CRI >90	
Optic Flood 29°	
Finishing Steel - graphite	
Luminaire luminous flux 703 lm	
Luminous efficiency 88 lm/W	
MacAdam color tolerance 3	
Power supply/transformer Not included	
Protocol See power supply	
Energy efficiency class D	
Weight 0.3 Kg	
Dimension H700 Ø120 mm	
IP Grade Ip66	
Protection Class Class III appliance	





ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 1

LUCIFERO'S SRL with sole shareholder - via del Tappezziere, 3 - 40138 Bologna - Italy - +39 051 6014276 - assistenza@luciferos.it - customercare@luciferos.it