

## Focus T55 Track

code FS602.9U30F/01



### PRODUCT DESCRIPTION

3 phase mixed-system electrified track, with two additional conductors to manage a general digital or analogic signal (1-10V, DALI, dmx, lon, eib, etc.). Body made of powder coated extruded aluminum, housing four copper conductors (three phases and one neutral 16A) and two copper conductors for the data signal, insulated in PVC. 4mm<sup>2</sup>-section earth conductor incorporated in the extrusion. Arranged for ON/OFF separate three-circuit switch or management through digital signal (DALI). EN 60570 certified. Its installation must be accomplished by highly qualified personnel. Four possible installation systems: directly on ceiling/wall by using the needlepoints provided on the track, on ceiling/wall by using the metal clips (order separately), hanging by using the suspension kits (order separately) or recessed, without exceeding the maximum loads. To be used with projectors provided with Eurostandard adapter (for standard use) or with DALI-Stucchi adapter (for DALI use).

### PRODUCT SPECS

|                              |                       |
|------------------------------|-----------------------|
| Installation method          | Track                 |
| Light source                 | LED                   |
| Absorbed power               | 12 W                  |
| Color temperature            | 3000K                 |
| Color rendering index CRI    | >90                   |
| Optic                        | Flood                 |
| Finishing                    | White                 |
| Luminous flux of the product | 1350 lm               |
| Luminous efficiency          | 113 lm/W              |
| MacAdam color tolerance      | 3                     |
| Life time estimate           | 50000h Ta 25° L80 B10 |
| Energy efficiency class      | E                     |
| Dimension                    | H160 Ø55 mm           |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS





