



File Pro Track System

code FP014.927WID/01



















PRODUCT DESCRIPTION

Direct light indoor lamp for track system three phases made of extruded 6060 aluminium; assembled and wired on extruded aluminium; color rendering index CRI >90. Protocol Dimmable Dali; Lamp with white powder-coated finish; high efficiency professional optics in polycarbonate; beam 60° UGR. IP40 protection rating.

PRODUCT SPECS

Light source LED pro Absorbed power 21,4 W Color temperature 2700K Color rendering index CRI >90 Optic 60° UGR Finishing White Luminous flux of the product 3750 Im Luminous efficiency 175 Im/W MacAdam color tolerance 3 Durata media stimata 3SDCM 50000h L90 B10 Ta 25°C Power supply/transformer Included Protocol Dimmable Dali Energy efficiency class D Weight 3.2 Kg Dimension L582 mm	Installation method	Track
Color temperature 2700K Color rendering index CRI >90 Optic 60° UGR Finishing White Luminous flux of the product 3750 lm Luminous efficiency 175 lm/W MacAdam color tolerance 3 Durata media stimata 3SDCM 50000h L90 B10 Ta 25°C Power supply/transformer Included Protocol Dimmable Dali Energy efficiency class D Weight 3.2 Kg	Light source	LED pro
Color rendering index CRI >90 Optic 60° UGR Finishing White Luminous flux of the product 3750 Im Luminous efficiency 175 Im/W MacAdam color tolerance 3 Durata media stimata 3SDCM 50000h L90 B10 Ta 25°C Power supply/transformer Included Protocol Dimmable Dali Energy efficiency class D Weight 3.2 Kg	Absorbed power	21,4 W
Optic 60° UGR Finishing White Luminous flux of the product 3750 lm Luminous efficiency 175 lm/W MacAdam color tolerance 3 Durata media stimata 3SDCM 50000h L90 B10 Ta 25°C Power supply/transformer Included Protocol Dimmable Dali Energy efficiency class D Weight 3.2 Kg	Color temperature	2700K
Finishing Luminous flux of the product Luminous efficiency MacAdam color tolerance Durata media stimata Durata media stimata Protocol Protocol Energy efficiency class Weight White 3750 lm 175 lm/W 3SDCM 50000h L90 B10 Ta 25°C Included Dimmable Dali Energy efficiency class D Weight	Color rendering index CRI	>90
Luminous flux of the product 3750 lm Luminous efficiency 175 lm/W MacAdam color tolerance 3 Durata media stimata 3SDCM 50000h L90 B10 Ta 25°C Power supply/transformer Included Protocol Dimmable Dali Energy efficiency class D Weight 3.2 Kg	Optic	60° UGR
Luminous efficiency 175 lm/W MacAdam color tolerance 3 Durata media stimata 3SDCM 50000h L90 B10 Ta 25°C Power supply/transformer Included Protocol Dimmable Dali Energy efficiency class D Weight 3.2 Kg	Finishing	White
MacAdam color tolerance 3 Durata media stimata 3SDCM 50000h L90 B10 Ta 25°C Power supply/transformer Included Protocol Dimmable Dali Energy efficiency class D Weight 3.2 Kg	Luminous flux of the product	3750 lm
Durata media stimata 3SDCM 50000h L90 B10 Ta 25°C Power supply/transformer Included Protocol Dimmable Dali Energy efficiency class D Weight 3.2 Kg	Luminous efficiency	175 lm/W
Durata media stimata Ta 25°C Power supply/transformer Included Protocol Energy efficiency class D Weight 3.2 Kg	MacAdam color tolerance	3
Protocol Dimmable Dali Energy efficiency class D Weight 3.2 Kg	Durata media stimata	
Energy efficiency class D Weight 3.2 Kg	Power supply/transformer	Included
Weight 3.2 Kg	Protocol	Dimmable Dali
<u> </u>	Energy efficiency class	D
Dimension L582 mm	Weight	3.2 Kg
	Dimension	L582 mm
IP Grade IP20	IP Grade	IP20

WEB PAGE







