



File Pro Track System

code FP024.930EWD/01





















PRODUCT DESCRIPTION

Direct light indoor lamp for track system three phases made of extruded 6060 aluminium; assembled and wired on extruded aluminium; color rendering index CRI >90. Protocol Dimmable Dali; Lamp with white powder-coated finish; high efficiency professional optics in polycarbonate; beam Extra wide 110. IP40 protection rating.

PRODUCT SPECS

| Light source Absorbed power 96 W Color temperature 3000K Color rendering index CRI Optic Extra wide 110 Finishing White Luminous flux of the product Luminous efficiency Luminous efficiency Lie D pro W W Lie D pro W W 100 Lie D pro W 100 Lie D pro 100 100 100 100 100 100 100 1 | Installation method | Track |
|---|------------------------------|--------------------|
| Color temperature 3000K Color rendering index CRI >90 Optic Extra wide 110 Finishing White Luminous flux of the product 13958 Im | Light source | LED pro |
| Color rendering index CRI >90 Optic Extra wide 110 Finishing White Luminous flux of the product 13958 lm | Absorbed power | 96 W |
| Optic Extra wide 110 Finishing White Luminous flux of the product 13958 Im | Color temperature | 3000K |
| Finishing White Luminous flux of the product 13958 lm | Color rendering index CRI | >90 |
| Luminous flux of the product 13958 lm | Optic | Extra wide 110 |
| · | Finishing | White |
| Luminous efficiency 145 lm/W | Luminous flux of the product | 13958 lm |
| | Luminous efficiency | 145 lm/W |
| MacAdam color tolerance 3 | MacAdam color tolerance | 3 |
| Durata media stimata 3SDCM 50000h L90 B10 Ta 25°C | Durata media stimata | 0020 00000 200 2.0 |
| Power supply/transformer Included | Power supply/transformer | Included |
| Protocol Dimmable Dali | Protocol | Dimmable Dali |
| Energy efficiency class D | Energy efficiency class | D |
| Weight 5.4 Kg | Weight | 5.4 Kg |
| Dimension L1726 mm | Dimension | L1726 mm |
| IP Grade IP20 | IP Grade | IP20 |

WEB PAGE



ASSEMBLY INSTRUCTIONS



