




File Pro Track System

code FP024.940DF/01



PRODUCT DESCRIPTION

Direct light indoor lamp for track system three phases made of extruded 6060 aluminium; assembled and wired on extruded aluminium; color rendering index CRI >90. Protocol On/Off; Lamp with white powder-coated finish; high efficiency professional optics in polycarbonate; beam : IP40 protection rating.

PRODUCT SPECS

Installation method	Track
Light source	LED pro
Absorbed power	96 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Diffused
Finishing	White
Luminous flux of the product	12795 lm
Luminous efficiency	133 lm/W
MacAdam color tolerance	3
Life time estimate	3SDCM 50000h L90 B10 Ta 25°C
Protocol	On/Off
Energy efficiency class	D
Weight	5.4 Kg
Dimension	L1726 mm
IP Grade	IP20
Power supply	220-240V 50-60Hz

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

Page 1 / 2

