

## File Pro Suspension

code FP006.930EW/01




### PRODUCT DESCRIPTION

Direct light indoor suspension lamp made of extruded 6060 aluminium; assembled and wired on extruded aluminium; color rendering index CRI >90. Protocol On/Off. Complete with steel suspension cables with micrometric adjuster to adjust the height and balance stabilizer to adjust the horizontality of the product; Lamp with white powder-coated finish; high efficiency professional optics in polycarbonate; beam . IP40 protection rating.

### PRODUCT SPECS

|                              |                                 |
|------------------------------|---------------------------------|
| Installation method          | Suspension                      |
| Light source                 | LED pro                         |
| Absorbed power               | 82 W                            |
| Color temperature            | 3000K                           |
| Color rendering index CRI    | >90                             |
| Optic                        | Extra wide 110                  |
| Finishing                    | White                           |
| Luminous flux of the product | 11645 lm                        |
| Luminous efficiency          | 142 lm/W                        |
| MacAdam color tolerance      | 3                               |
| Life time estimate           | 3SDCM 50000h L90 B10<br>Ta 25°C |
| Protocol                     | On/Off                          |
| Energy efficiency class      | D                               |
| Weight                       | 5.2 Kg                          |
| Dimension                    | L1440 mm                        |
| IP Grade                     | IP40                            |
| Power supply                 | 220-240V 50-60Hz                |



### WEB PAGE



### ASSEMBLY INSTRUCTIONS

