

## File Pro Suspension

code FP012.940NR/01




### PRODUCT DESCRIPTION

Direct light indoor suspension lamp made of extruded 6060 aluminium; assembled and wired on extruded aluminium; color rendering index CRI >90. Protocol On/Off. Complete with steel suspension cables with micrometric adjuster to adjust the height and balance stabilizer to adjust the horizontality of the product; Lamp with white powder-coated finish; high efficiency professional optics in polycarbonate; beam . IP40 protection rating.

### PRODUCT SPECS

|                              |                        |
|------------------------------|------------------------|
| Installation method          | Suspension             |
| Light source                 | LED pro                |
| Absorbed power               | 160 W                  |
| Color temperature            | 4000K                  |
| Color rendering index CRI    | >90                    |
| Optic                        | Narrow 30              |
| Finishing                    | White                  |
| Luminous flux of the product | 25756 lm               |
| Luminous efficiency          | 161 lm/W               |
| MacAdam color tolerance      | 3                      |
| Life time estimate           | 50000h L90 B10 Ta 25°C |
| Protocol                     | On/Off                 |
| Energy efficiency class      | D                      |
| Weight                       | 10 Kg                  |
| Dimension                    | L2870 mm               |
| IP Grade                     | IP40                   |
| Power supply                 | 220-240V 50-60Hz       |



### WEB PAGE



### ASSEMBLY INSTRUCTIONS

