



Fifty5 Pro Suspension LED

code FT023.9HCDFD/01







PRODUCT DESCRIPTION

Linear lighting fixtures, in extruded aluminum 55x55mm, for ceiling, suspension. Embossed painted finish. Screens for diffused light in opal polycarbonate, for the PRO version are available optics with different beam openings. Might be equipped, if necessary, with spectra for horticulture. IP40 / IP43. Available default modules and modular system.

PRODUCT SPECS

Installation method	Suspension
Light source	Led
Absorbed power	46,8 W
Color temperature	Horticulture
Color rendering index CRI	>90
Optic	Diffused
Finishing	White
Power supply/transformer	Included
Protocol	Dimmable
Energy efficiency class	D
Dimension	L1142 mm
IP Grade	IP20
Protection Class	Class I appliance





WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 1

LUCIFERO'S SRL with sole shareholder - via del Tappezziere, 3 - 40138 Bologna - Italy - +39 051 6014276 - assistenza@luciferos.it - customercare@luciferos.it