



Iride Outdoor 114L

code IR06IP.930FD/01









E A IKO7 (LED) KK (E

PRODUCT DESCRIPTION

Outdoor ceiling/wall projector complete with led 26 W, beam Flood 25°, colour rendering index CRI>90. Colour finish white. Body lamp and optical group made of die-cast aluminum powder-coated, aluminum joint, rotation of the optical group of 355 ?. on the vertical axis and 90 ?. on the horizontal axis. Snooter in lamp finish or finishing choice. High performance lens. Possibility of insertion of Honey Comb filter.

PRODUCT SPECS

| Light sourceLed-enAbsorbed power26 WColor temperature3000KColor rendering index CRI>90OpticFlood 25°FinishingWhiteLuminaire luminous flux2950 lmLuminous efficiency113 lm/WPower supply/transformerIncludedProtocolDimmableEnergy efficiency classEDimensionØ114 mm | Installation method | Wall surface mounted, Ceiling surface mounted |
|---|---------------------------|--|
| Color temperature3000KColor rendering index CRI>90OpticFlood 25°FinishingWhiteLuminaire luminous flux2950 lmLuminous efficiency113 lm/WPower supply/transformerIncludedProtocolDimmableEnergy efficiency classE | Light source | Led-en |
| Color rendering index CRI>90OpticFlood 25°FinishingWhiteLuminaire luminous flux2950 ImLuminous efficiency113 Im/WPower supply/transformerIncludedProtocolDimmableEnergy efficiency classE | Absorbed power | 26 W |
| OpticFlood 25°FinishingWhiteLuminaire luminous flux2950 lmLuminous efficiency113 lm/WPower supply/transformerIncludedProtocolDimmableEnergy efficiency classE | Color temperature | 3000K |
| FinishingWhiteLuminaire luminous flux2950 lmLuminous efficiency113 lm/WPower supply/transformerIncludedProtocolDimmableEnergy efficiency classE | Color rendering index CRI | >90 |
| Luminaire luminous flux2950 lmLuminous efficiency113 lm/WPower supply/transformerIncludedProtocolDimmableEnergy efficiency classE | Optic | Flood 25° |
| Luminous efficiency113 lm/WPower supply/transformerIncludedProtocolDimmableEnergy efficiency classE | Finishing | White |
| Power supply/transformerIncludedProtocolDimmableEnergy efficiency classE | Luminaire luminous flux | 2950 lm |
| Protocol Dimmable Energy efficiency class E | Luminous efficiency | 113 lm/W |
| Energy efficiency class E | Power supply/transformer | Included |
| | Protocol | Dimmable |
| Dimension Ø114 mm | Energy efficiency class | E |
| | Dimension | Ø114 mm |

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 2



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.