



## Iride Outdoor 114L

code IR07IP.927FD/01







## TECHNICAL SHEET 15.05.2024



## **PRODUCT DESCRIPTION**

Outdoor ceiling/wall projector complete with led 34 W, beam Flood 25°, colour rendering index CRI>90. Colour finish white. Body lamp and optical group made of die-cast aluminum powder-coated, aluminum joint, rotation of the optical group of 355 ?. on the vertical axis and 90 ?. on the horizontal axis. Snooter in lamp finish or finishing choice. High performance lens. Possibility of insertion of Honey Comb filter.

## PRODUCT SPECS

Installation method	Wall surface mounted, Ceiling surface mounted
Light source	Led
Absorbed power	34 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Flood 25°
Finishing	White
Luminaire luminous flu	x 3200 lm
Luminous efficiency	94 lm/W
MacAdam color tolerance	3
Power supply/transformer	Included
Protocol	Dimmable
Energy efficiency class	; D
Dimension	Ø114 mm





ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 2



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.