




Iride Outdoor 86L

code IR04IP.940F/01









TECHNICAL SHEET 15.05.2024

PRODUCT DESCRIPTION

Outdoor ceiling/wall projector complete with led 18 W, beam Flood 24°, colour rendering index CRI>90. Colour finish white. Body lamp and optical group made of die-cast aluminum powder-coated, aluminum joint, rotation of the optical group of 355 ?. on the vertical axis and 90 ?. on the horizontal axis. Snooter in lamp finish or finishing choice. High performance lens. Possibility of insertion of Honey Comb filter.

PRODUCT SPECS

| Installation method | Wall surface mounted, Ceiling surface mounted |
|-----------------------------|--|
| Light source | Led |
| Absorbed power | 18 W |
| Color temperature | 4000K |
| Color rendering index CRI | >90 |
| Optic | Flood 24° |
| Finishing | White |
| Luminaire luminous flux | (2500 lm |
| Luminous efficiency | 139 lm/W |
| MacAdam color tolerance | 3 |
| Durata media stimata | 50000h Ta 25° L70B10 |
| Power supply/transformer | Included |
| Protocol | On/Off |
| Voltage | 230 V |
| Energy efficiency class | D |
| Dimension | Ø86 mm |
| | |

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 2

