


Iride Outdoor 86L

code IR05IP.940FD/01











PRODUCT DESCRIPTION

Outdoor ceiling/wall projector complete with led 26 W, beam Flood 24°, colour rendering index CRI>90. Colour finish white. Body lamp and optical group made of die-cast aluminum powder-coated, aluminum joint, rotation of the optical group of 355 ?. on the vertical axis and 90 ?. on the horizontal axis. Snooter in lamp finish or finishing choice. High performance lens. Possibility of insertion of Honey Comb filter.

PRODUCT SPECS

Light sourceLedAbsorbed power26 WColor temperature4000KColor rendering index CRI>90OpticFlood 24°FinishingWhiteLuminaire luminous flux3250 ImLuminous efficiency125 Im/WPower supply/transformerIncludedProtocolDimmableEnergy efficiency classEDimensionØ86 mm	Installation method	Wall surface mounted, Ceiling surface mounted
Color temperature4000KColor rendering index CRI>90OpticFlood 24°FinishingWhiteLuminaire luminous flux 3250 lmLuminous efficiency125 lm/WPower supply/transformerIncludedProtocolDimmableEnergy efficiency classE	Light source	Led
Color rendering index CRI>90OpticFlood 24°FinishingWhiteLuminaire luminous flux 3250 lmLuminous efficiency125 lm/WPower supply/transformerIncludedProtocolDimmableEnergy efficiency classE	Absorbed power	26 W
CRI >90 Optic Flood 24° Finishing White Luminaire luminous flux 3250 lm Luminous efficiency 125 lm/W Power supply/transformer Included Protocol Dimmable Energy efficiency class E	Color temperature	4000K
FinishingWhiteLuminaire luminous flux 3250 lmLuminous efficiency125 lm/WPower supply/transformerIncludedProtocolDimmableEnergy efficiency classE	•	>90
Luminaire luminous flux 3250 lm Luminous efficiency 125 lm/W Power Included supply/transformer Dimmable Protocol Dimmable Energy efficiency class E	Optic	Flood 24°
Luminous efficiency125 lm/WPower supply/transformerIncludedProtocolDimmableEnergy efficiency classE	Finishing	White
Power supply/transformerIncludedProtocolDimmableEnergy efficiency classE	Luminaire luminous flux 3250 lm	
Supply/transformer Included Protocol Dimmable Energy efficiency class E	Luminous efficiency	125 lm/W
Energy efficiency class E		Included
	Protocol	Dimmable
Dimension Ø86 mm	Energy efficiency class	E
	Dimension	Ø86 mm





ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 2

