



Iride Outdoor 86L

code IR05IP.940S/01







TECHNICAL SHEET 17.05.2024



PRODUCT DESCRIPTION

Outdoor ceiling/wall projector complete with led 26 W, beam Spot 19°, colour rendering index CRI>90. Colour finish white. Body lamp and optical group made of die-cast aluminum powder-coated, aluminum joint, rotation of the optical group of 355 ?. on the vertical axis and 90 ?. on the horizontal axis. Snooter in lamp finish or finishing choice. High performance lens. Possibility of insertion of Honey Comb filter.

PRODUCT SPECS

Installation method	Wall surface mounted, Ceiling surface mounted
Light source	Led
Absorbed power	26 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Spot 19°
Finishing	White
Luminaire luminous flux	3250 lm
Luminous efficiency	125 lm/W
Power supply/transformer	Included
Protocol	On/Off
Energy efficiency class	E
Dimension	Ø86 mm

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 2

