



Iride Outdoor 114S

code IR03IP.927WD/01







TECHNICAL SHEET 17.05.2024



PRODUCT DESCRIPTION

Outdoor ceiling/wall projector complete with led 34 W, beam Wide 36°, colour rendering index CRI>90. Colour finish bianco. Body lamp and optical group made of die-cast aluminum powder-coated, aluminum joint, rotation of the optical group of 355 ?. on the vertical axis and 90 ?. on the horizontal axis. Snooter in lamp finish or finishing choice. High performance lens. Possibility of insertion of Honey Comb filter.

PRODUCT SPECS

Installation method	Wall surface mounted, Ceiling surface mounted
Light source	Led
Absorbed power	34 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Wide 36°
Finishing	Bianco
Luminaire luminous flux	3200 lm
Luminous efficiency	94 lm/W
MacAdam color tolerance	3
Power supply/transformer	Included
Protocol	Dimmable
Energy efficiency class	D
Dimension	Ø114 mm

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 2

LUCIFERO'S SRL with sole shareholder - via del Tappezziere, 3 - 40138 Bologna - Italy - +39 051 6014276 - assistenza@luciferos.it - customercare@luciferos.it



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.