



### Leva 15 recessed - kit

code LV015K..935S/01















# PRODUCT DESCRIPTION

Integrated LED Chip On Board light fixture. Recessed installation with stop. Luminaire body in extruded painted aluminum white. Optical groups complete with LED chip on board, lens, anti-glare housing. Optics 20° UGR<16. Protection rating IP20.

# **PRODUCT SPECS**

Light source Absorbed power Absorbed power Color temperature 3500K Color rendering index CRI Optic Spot 20° Finishing White Luminous flux of the product Luminous efficiency 99 lm/W MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Energy efficiency class E Weight 0.30 Kg Dimension L450xW27xH60 mm Hole size 34X456 mm Power supply/Transformer Not included Protocol See power supply	Installation method	Recessed with frame
Color temperature 3500K  Color rendering index CRI >90  Optic Spot 20°  Finishing White  Luminous flux of the product 3269 Im  Luminous efficiency 99 Im/W  MacAdam color tolerance 2  Life time estimate 50000h Ta 25° L90B10  Energy efficiency class E  Weight 0.30 Kg  Dimension L450xW27xH60 mm  Hole size 34X456 mm  Power supply/Transformer Not included	Light source	LED
Color rendering index CRI >90 Optic Spot 20° Finishing White Luminous flux of the product 3269 Im Luminous efficiency 99 Im/W MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Energy efficiency class E Weight 0.30 Kg Dimension L450xW27xH60 mm Hole size 34X456 mm Power supply/Transformer Not included	Absorbed power	15x2,2 W
Optic Spot 20° Finishing White Luminous flux of the product 3269 Im Luminous efficiency 99 Im/W MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Energy efficiency class E Weight 0.30 Kg Dimension L450xW27xH60 mm Hole size 34X456 mm Power supply/Transformer Not included	Color temperature	3500K
Finishing White Luminous flux of the product 3269 lm Luminous efficiency 99 lm/W MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Energy efficiency class E Weight 0.30 Kg Dimension L450xW27xH60 mm Hole size 34X456 mm Power supply/Transformer Not included	Color rendering index CRI	>90
Luminous flux of the product  Luminous efficiency  MacAdam color tolerance  Life time estimate  Energy efficiency class  Weight  Dimension  Hole size  Power supply/Transformer  3269 Im  3269 Im  3269 Im  3269 Im  490 Im/W  50000h Ta 25° L90B10  Energy efficiency class  E  40000h Ta 25° L90B10  L450xW27xH60 mm  AVA456 mm  Not included	Optic	Spot 20°
Luminous efficiency     99 lm/W       MacAdam color tolerance     2       Life time estimate     50000h Ta 25° L90B10       Energy efficiency class     E       Weight     0.30 Kg       Dimension     L450xW27xH60 mm       Hole size     34X456 mm       Power supply/Transformer     Not included	Finishing	White
MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Energy efficiency class E Weight 0.30 Kg Dimension L450xW27xH60 mm Hole size 34X456 mm Power supply/Transformer Not included	Luminous flux of the product	3269 lm
Life time estimate 50000h Ta 25° L90B10  Energy efficiency class E  Weight 0.30 Kg  Dimension L450xW27xH60 mm  Hole size 34X456 mm  Power supply/Transformer Not included	Luminous efficiency	99 lm/W
Energy efficiency class E Weight 0.30 Kg Dimension L450xW27xH60 mm Hole size 34X456 mm Power supply/Transformer Not included	MacAdam color tolerance	2
Weight         0.30 Kg           Dimension         L450xW27xH60 mm           Hole size         34X456 mm           Power supply/Transformer         Not included	Life time estimate	50000h Ta 25° L90B10
Dimension L450xW27xH60 mm  Hole size 34X456 mm  Power supply/Transformer Not included	Energy efficiency class	E
Hole size 34X456 mm Power supply/Transformer Not included	Weight	0.30 Kg
Power supply/Transformer Not included	Dimension	L450xW27xH60 mm
	Hole size	34X456 mm
Protocol See power supply	Power supply/Transformer	Not included
	Protocol	See power supply

**WEB PAGE** 



**ASSEMBLY** 



### **MANDATORY ACCESSORIES**

### Accessori Leva Wallbox F 15



code LV015F/01

Recessed with frame uncategorized wallbox for false ceiling. Bianco finishing wallbox for false ceiling



# AE700.32C1.MP (Copia) (Copia)



code AE700.30C.MP-1

Electronic power supply current



# **OPTIONAL ACCESSORIES**

### Wallbox for brick wall and concrete - Leva15



code CCLV15

Formwork for masonry and concrete, suitable for Leva15. Internal length 457mm - external length 459,4mm

