

#### Convex recessed frame fisso

250

350













code CV018.927F/01







### PRODUCT DESCRIPTION

Recessed direct light lamp with circular stop complete with led 8 W or 12 W, color rendering index CRI92. Color finish white. Optical body made of die-cast aluminum, passive dissipation with black anodized aluminum heatsink high thermal efficiency. 99.9% aluminium finish optics, backlit light source with anti-glare effect; degree of protection IP20/23. Powder coated.

# PRODUCT SPECS

Installation method	recessed with frame
Light source	LED
Absorbed power	8 W / 12 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Flood 27°
Finishing	White
Luminous flux of the product	1032 lm / 1257 lm
Luminous efficiency	129 lm/W / 105 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Life time estimate  Energy efficiency class	
	ta25°
Energy efficiency class	ta25° D
Energy efficiency class Weight	ta25° D 0.35 Kg
Energy efficiency class Weight Dimension	ta25° D 0.35 Kg H90 Ø84 mm
Energy efficiency class Weight Dimension Hole size	ta25° D 0.35 Kg H90 Ø84 mm Ø 75 mm
Energy efficiency class Weight Dimension Hole size IP Grade	ta25° D 0.35 Kg H90 Ø84 mm Ø 75 mm IP20
Energy efficiency class Weight Dimension Hole size IP Grade Protection Class	ta25° D 0.35 Kg H90 Ø84 mm Ø 75 mm IP20 Class III appliance

**WEB PAGE** 



**ASSEMBLY** INSTRUCTIONS



### **MANDATORY ACCESSORIES**

## AE350.16C (Copia)



code AE350.15C

Electronic power supply current

## AE500.20C1 (Copia)



code AE500.20C.MP

Electronic power supply current

### **OPTIONAL ACCESSORIES**

## Optional accessory to transform Convex in trimless recessed



code CV030

Accessory to transform Convex into trimless recessed. 100 mm outer diameter

