


## Irde recessed frame fixed

code IR20.927F/01





### PRODUCT DESCRIPTION

Recessed indoor projector with fixed projection, complete with led 26 W, color rendering index CRI >90. Lamp with color finish white. Lamp body and optical group made of powder-coated die-cast aluminium, springs in harmonic steel for quick installation. High performance polycarbonate lens. UGR<19

### PRODUCT SPECS

|                              |                                 |
|------------------------------|---------------------------------|
| Installation method          | recessed with frame             |
| Light source                 | LED                             |
| Absorbed power               | 26 W                            |
| Color temperature            | 2700K                           |
| Color rendering index CRI    | >90                             |
| Optic                        | Flood 24°                       |
| Finishing                    | White                           |
| Luminous flux of the product | 2411 lm                         |
| Luminous efficiency          | 93 lm/W                         |
| Life time estimate           | 3SDCM 50000h L90 B10<br>Ta 25°C |
| Energy efficiency class      | E                               |
| Dimension                    | H98.5 Ø114 mm                   |
| IP Grade                     | IP20                            |
| Power supply/Transformer     | Not included                    |
| Protocol                     | See power supply                |



### WEB PAGE




### ASSEMBLY INSTRUCTIONS



## OPTIONAL ACCESSORIES

### Private:



code L114R

Non-reflective accessory lens with a honeycomb structure, diameter 86 mm.

Technical Sheet



