


**Minifile Mix suspension direct light**

code MM005.930D/01

**PRODUCT DESCRIPTION**

Direct and diffused light indoor suspension lamp made of extruded aluminum 6060, complete with one power led line element 19.2W complete with opal polycarbonate cover + 1 Spot led 8W, optical body made of aluminum, rotation joint 90° on horizontal axis and 355° on vertical axis, polycarbonate lens, anti-glare front snooter. Integrated power supply. Color finish white made by epoxy powder coating. Equipped with harmonic steel springs for installation in Tools free profile. Color rendering index CRI>90. IP20 degree of protection.

**PRODUCT SPECS**

|                              |                                 |
|------------------------------|---------------------------------|
| Installation method          | Suspension                      |
| Light source                 | Linea Led                       |
| Absorbed power               | 19,2 W / 8 W                    |
| Color temperature            | 3000K                           |
| Color rendering index CRI    | >90                             |
| Finishing                    | White                           |
| Luminous flux of the product | 2976 lm / 840 lm                |
| Luminous efficiency          | 155 lm/W / 105 lm/W             |
| MacAdam color tolerance      | 3                               |
| Life time estimate           | 3SDCM 50000h L90 B10<br>Ta 25°C |
| Protocol                     | Dimmable Dali / Touch & Dimm    |
| Energy efficiency class      | E                               |
| Weight                       | 2.20 Kg                         |
| Dimension                    | L1140xH92 mm                    |

**WEB PAGE****ASSEMBLY INSTRUCTIONS**