

Manine outdoor diffused 90-V doube emission vertical

code MN004P.930/01



14°

105°


90° 90 75°

60°

459

30°

150















PRODUCT DESCRIPTION

Outdoor internal corner luminaire, bi-emission for diffuse lighting. Complete optical unit with professional LED sources 12 W, complete with ballast. 90° internal angle version with 120x120 mm metal body, 30 mm wall projection white. Degree of protection IP54.

PRODUCT SPECS

Installation method	Wall surface mounted
Light source	Lampadine
Absorbed power	2x6 W
Color temperature	3000K
Color rendering index CRI	>90
Finishing	White
Luminous flux of the product	300 lm
Luminous efficiency	25 lm/W
Life time estimate	3SDCM 50000h L80 B10 ta 25°C
Weight	0.82 Kg
Dimension	L120xH120 mm
IP Grade	IP54
Power supply	220-240V 50-60Hz





ASSEMBLY



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

MANINE LED

cd/klm

1000

00

1059

90°

75° 609

309