LED line 5 meters roll - IP20

code ST05.30.5

| 24V | CRI >90 | IP20 | Ⓐ | UKCA | CE |

PRODUCT DESCRIPTION

High efficiency led strip with double-sided adhesive and 8 mm wide support on 5 meters coil, to be powered with 24vdc voltage stabilized drivers. Degree of protection IP20. Insulation class III

5000

PRODUCT SPECS

Installation method	system
Light source	Linea-led
Absorbed power	5,5 W
Color temperature	3000K
Color rendering index CRI	80
Luminaire luminous flux	1350 lm
Luminous efficiency	49 lm/W
Power supply/transformer	Not included
Weight	0.18 Kg
Dimension	L5000Wx8 mm
IP Grade	IP20

CUTS

IP20   IP67

8							
125	8	8		10	10	12	
	62,5	50	10	62,5	50	42	
			6,25				
5W	9,6W	11W	22W	9,6W	11W	18W	

WEB PAGE

ASSEMBLY INSTRUCTIONS

Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.
Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.
We reserve the right to make changes to our products at any time.