

Ci 35 Fixed

code LT1167.940F/01




















PRODUCT DESCRIPTION


Round recessed spotlight. Wall/ceiling appliance

PRODUCT SPECS

Installation method	Recessed with frame
Light source	LED
Absorbed power	5 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Flood 22°
Finishing	White
Luminous flux of the product	628 lm
Luminous efficiency	126 lm/W
MacAdam color tolerance	2
Life time estimate	50000h L90 B10 ta 25°C
Energy efficiency class	D
Weight	0.13 Kg
Dimension	H80 Ø64 mm
Hole size	Ø 56 mm
IP Grade	IP20
Protection Class	Class III appliance
Product Spec	Circular shape
Power supply/Transformer	Not included
Protocol	See power supply







WEB PAGE







Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

OPTIONAL ACCESSORIES

Accessori Wallbox Wallbox Cl35 e Cl35/35F



code LT9061

Galvanized metal wallbox to be recessed in brick walls or reinforced concrete to fit the article Cl35 and Cl35F $\,$

