



### **Guide System Spot focus 90**

code GU006.927W/01

4





150

٥°

15°

30°

30°



#### **PRODUCT DESCRIPTION**

Cylindrical projector in extruded aluminium, adjustable on the vertical axis of 355, and on the horizontal axis of +/- 90, equipped with hook for installation on the profile; powder coating; with COB technology (Chip on Board) for maximum efficiency; absence of multiple shadows; Energy efficient LEDs with high color rendering; secondary lens in high transparency pmma; optical units available as accessories with replacement without tools; available accessories such as honey comb, elipsoid lens, asymmetric lens, satined lens. Color finish bianco.

#### PRODUCT SPECS

Installation method	system
Light source	Led
Absorbed power	32 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Wide 38°
Finishing	Bianco
Luminous flux of the product	4662 lm
Luminous efficiency	146 lm/W
MacAdam color tolerance	3
Durata media stimata	3SDCM 50000h L90 B10 ta 25°C
Durata media stimata Power supply/transformer	
	ta 25°C
Power supply/transformer	ta 25°C Not included
Power supply/transformer Protocol	ta 25°C Not included See power supply
Power supply/transformer Protocol Energy efficiency class	ta 25°C Not included See power supply E
Power supply/transformer Protocol Energy efficiency class Weight	ta 25°C Not included See power supply E 0.94 Kg
Power supply/transformer Protocol Energy efficiency class Weight Dimension	ta 25°C Not included See power supply E 0.94 Kg H110 Ø90 mm

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 3

LUCIFERO'S SRL with sole shareholder - via del Tappezziere, 3 - 40138 Bologna - Italy - +39 051 6014276 - assistenza@luciferos.it - customercare@luciferos.it

#### **OPTIONAL ACCESSORIES**

### Accessori Lens With Ring Satin lens with ring ø85



code L085S.A uncategorized. White finishing

0

code L085S.A uncategorized. Black finishing

### Accessori Lens With Ring Asymmetric lens with ring ø85



code L085A.A uncategorized. White finishing



code L085A.A uncategorized. Black finishing

# Accessori Lens With Ring Elipsoid lens with ring ø85



code L085E.A

uncategorized. White finishing







**Technical Sheet** 



**Technical Sheet** 



**Technical Sheet** 





code L085E.A uncategorized. Black finishing

## Accessori Lens With Ring Honeycomb louver with ring ø85



code L085R.A uncategorized. White finishing



code L085R.A uncategorized. Black finishing



**Technical Sheet** 



**Technical Sheet** 



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.