

Guide System Spot focus 90

code GU006.930S/01






















PRODUCT DESCRIPTION

Cylindrical projector in extruded aluminium, adjustable on the vertical axis of 355, and on the horizontal axis of +/- 90, equipped with hook for installation on the profile; powder coating; with COB technology (Chip on Board) for maximum efficiency; absence of multiple shadows; Energy efficient LEDs with high color rendering; secondary lens in high transparency pmma; optical units available as accessories with replacement without tools; available accessories such as honey comb, elipsoid lens, asymmetric lens, satined lens. Color finish bianco.

PRODUCT SPECS

Installation method	system
Light source	Led
Absorbed power	32 W
Color temperature	3000K
Color rendering index CRI	>90
Optic	Spot 15°
Finishing	Bianco
Luminous flux of the product	4662 lm
Luminous efficiency	146 lm/W
MacAdam color tolerance	3
Durata media stimata	3SDCM 50000h L90 B10 ta 25°C
Power supply/transformer	Not included
Protocol	See power supply
Energy efficiency class	Е
Weight	0.94 Kg
Dimension	H110 Ø90 mm
IP Grade	IP20
Protection Class	Class III appliance
gruppi alimentatori	Corrente LED 900mA

WEB PAGE







OPTIONAL ACCESSORIES

Accessori Lens With Ring Satin lens with ring ø85



code L085S.A

uncategorized. White finishing



code L085S.A

uncategorized. Black finishing



Accessori Lens With Ring Asymmetric lens with ring ø85



code L085A.A

uncategorized. White finishing



code L085A.A

uncategorized. Black finishing



Accessori Lens With Ring Elipsoid lens with ring ø85



code L085E.A

uncategorized. White finishing





code L085E.A

uncategorized. Black finishing



Accessori Lens With Ring Honeycomb louver with ring ø85



code L085R.A

uncategorized. White finishing



code L085R.A

uncategorized. Black finishing



