

Nyx Tube T 35

code LTN30T.927F/01




















PRODUCT DESCRIPTION

Wall/ceiling recessed lamp, rpund section, direct light. Possibility to install total recessed or semi-recessed

PRODUCT SPECS

Installation method	Recessed with frame
Light source	LED
Absorbed power	5 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Flood 22°
Finishing	White
Luminous flux of the product	666 lm
Luminous efficiency	133 lm/W
MacAdam color tolerance	2
Life time estimate	50000h L90 B10 ta 25°C
Energy efficiency class	D
Dimension	H84/144 Ø40 mm
Hole size	Ø 65 mm
IP Grade	IP20/54
Protection Class	Class III appliance
Product Spec	Circular shape
Power supply/Transformer	Not included
Protocol	See power supply





NYX 35 TUBE LED 105° 105° cd/klm 90° 90° 75° 75° 60° 60° 1045 45° 45° 4180 η = 100 % 30° 15°

WEB PAGE







Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.