


Nyx Trimless Directional T50D - optic group

code LTN60K.927W/01




PRODUCT DESCRIPTION

Wall/ceiling recessed lamp, round section, direct light.
Possibility to install total recessed or semi-recessed

PRODUCT SPECS

Installation method	Trimless recessed
Light source	LED
Absorbed power	12 W / 18 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Wide 46°
Finishing	White
Luminous flux of the product	1325 lm / 2268 lm
Luminous efficiency	110 lm/W / 126 lm/W
MacAdam color tolerance	2
Life time estimate	25000h L90 B10 ta25°
Energy efficiency class	D
Weight	0.38 Kg
Dimension	H114 Ø70 mm
Hole size	Ø 90 mm
IP Grade	IP20
Protection Class	Class III appliance
Product Spec	Adjustable, Circular shape
Power supply/Transformer	Not included
Protocol	See power supply



WEB PAGE



ASSEMBLY INSTRUCTIONS



MANDATORY ACCESSORIES

Outer Casing Nyx T50D trimless for plasterbord




code LTN05A

Trimless recessed indoor wallbox for false ceiling

Technical Sheet



Accessori Wallbox Nyx For Brickwall T50D outer casing box for brick wall



code LTN05B

Trimless recessed indoor outer casing for brick wall square shape

Technical Sheet



AE350.16C (Copia)



code AE350.15C

Electronic power supply current

AE500.20C1



code AE500.20C1

Electronic power supply current