

## File H wall double emission

code F1H55.840XD/01





### PRODUCT DESCRIPTION

Direct and indirect light indoor wall lamp made of extruded aluminum 6060, complete with led; color rendering index CRI >90. Professional led modules assembled and wired on extruded aluminum heatsink with high performance reflector, equipped with harmonic steel springs for installation in the profile Tools free; wiring through 5 cables with quick coupling terminal blocks; protocol Dimmable Dali; polycarbonate with diffusing film. Protection rating IP40.

### PRODUCT SPECS

|                              |                         |
|------------------------------|-------------------------|
| Installation method          | Wall surface mounted    |
| Light source                 | LED                     |
| Absorbed power               | 2x44,8 W                |
| Color temperature            | 4000K                   |
| Color rendering index CRI    | >90                     |
| Optic                        | Microprismatic diffuser |
| Finishing                    | White                   |
| Luminous flux of the product | 7095 lm                 |
| Luminous efficiency          | 79 lm/W                 |
| MacAdam color tolerance      | 3                       |
| Life time estimate           | 50000h Ta 25° L80B10    |
| Protocol                     | Dimmable Dali           |
| Energy efficiency class      | D                       |
| Dimension                    | L1985 mm                |
| IP Grade                     | IP40                    |
| Power supply                 | 220-240V 50-60Hz        |



### WEB PAGE



### ASSEMBLY INSTRUCTIONS

