

## Cento3cento Outdoor

code IC110.840






















## 300 250 700



## PRODUCT DESCRIPTION

LED floor luminaire, for street furniture and orientation and service lighting, opal diffuser. Body in CementoPiuma, lightweight fibreglass concrete, with "smooth cement" finish made by hand. Aluminium optical unit complete with 3,9W LED source, integrated electronic power supply. Voltage In 220/240V 50/60hz and steel mounting plate for ground fixing, with anti-theft lock. Degree of protection IP65. WARNING: This product has been realized with hand crafted procedures and not industrial. Small imperfections, empty, subsidence and ripples of the surface are deliberately present and they are a feature of the product, proving the hand-made manufacturing procedure.

## **PRODUCT SPECS**

Installation method	Floor
Light source	LED
Absorbed power	3,9 W
Color temperature	4000K
Color rendering index CRI	>80
Luminous flux of the product	430 lm
Luminous efficiency	110 lm/W
Life time estimate	3SDCM 50000h L90 B10 Ta 25°C
Protocol	On/Off
Energy efficiency class	D
Weight	8 Kg
Dimension	L300xW100xH250 mm
IP Grade	IP65
Power supply	220-240V 50-60Hz

**WEB PAGE** 



**ASSEMBLY** 



