

**Minifile Openlight System Empty
profile ceiling/semi-recessed**

code MO000.3000/01

**PRODUCT DESCRIPTION**

Series of semi-recessed, ceiling-mounted or suspended fixtures for direct diffused lighting. For linear LED sources or T16 fluorescent seamless lamps. 230/240V 50/60Hz integrated electronic supply. Available both as default modules and as modules to be assembled in a system. Body in extruded aluminium, painted or anodized finish. Opal white polycarbonate diffuser and Light Proof system side-end caps. Degree of protection IP40 or IP43, according to the way that it is installed.

PRODUCT SPECS

Installation method	system
Finishing	White
Dimension	L3000 mm

WEB PAGE**ASSEMBLY
INSTRUCTIONS**

Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.
Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.
We reserve the right to make changes to our products at any time.

Page 1 / 4

OPTIONAL ACCESSORIES

Minifile Openlight System Couple of closure heads ceiling/semi-recessed/suspension version



code MO005/01

Series of semi-recessed, ceiling-mounted or suspended fixtures for direct diffused lighting. For linear LED sources or T16 fluorescent seamless lamps. 230/240V 50/60Hz integrated electronic supply. Available both as default modules and as modules to be assembled in a system. Body in extruded aluminium, painted or anodized finish. Opal white polycarbonate diffuser and Light Proof system side-end caps. Degree of protection IP40 or IP43, according to the way that it is installed.

Technical Sheet



Minifile Openlight System Single fixing bracket for semi-recessed version



code MO007

Series of semi-recessed, ceiling-mounted or suspended fixtures for direct diffused lighting. For linear LED sources or T16 fluorescent seamless lamps. 230/240V 50/60Hz integrated electronic supply. Available both as default modules and as modules to be assembled in a system. Body in extruded aluminium, painted or anodized finish. Opal white polycarbonate diffuser and Light Proof system side-end caps. Degree of protection IP40 or IP43, according to the way that it is installed.

Technical Sheet



Linear joint couple




code LTM211

Modular system of 30X30 mm single and bi-emission extruded aluminium profiles, for recessed, ceiling and suspension installation, with LED linear sources and 230/240V electronic ballasts. Its dimensions make it suitable for installation on radiant ceilings by means of appropriate bracket. Painted finish. Diffuser screens in opal polycarbonate and side closing heads with Light Proof system. Degree of protection IP20/ IP40.

Technical Sheet



Angle connector couple



code LTM211.90

Trimless, fully-retracting flush recessed modular systems for housing system profiles and MINIFILE, FILE, FILE 2, FILE 2 COMPLEMENTI, LEVA and FARETÈN finished modules for creating cuts of continuous light or where light modules alternate to voids, in plaster-board false-ceiling or false-walls or in concrete or brick walls. Painted or anodised extruded aluminium body, with a predefined length or cut to size. To be completed with side end caps and finishing cover for the empty spaces in a retracted position to determine an effect of solids and voids. Can also be used with LED linear light sources, to be completed with opal white PC diffusing screen and remote power supplies, to create retracted grooves of light.

Technical Sheet



Minifile Openlight System Diffuser



code MO004.1000

Series of semi-recessed, ceiling-mounted or suspended fixtures for direct diffused lighting. For linear LED sources or T16 fluorescent seamless lamps. 230/240V 50/60Hz integrated electronic supply. Available both as default modules and as modules to be assembled in a system. Body in extruded aluminium, painted or anodized finish. Opal white polycarbonate diffuser and Light Proof system side-end caps. Degree of protection IP40 or IP43, according to the way that it is installed.

Technical Sheet



code MO004.2000

Series of semi-recessed, ceiling-mounted or suspended fixtures for direct diffused lighting. For linear LED sources or T16 fluorescent seamless lamps. 230/240V 50/60Hz integrated electronic supply. Available both as default modules and as modules to be assembled in a system. Body in extruded aluminium, painted or anodized finish. Opal white polycarbonate diffuser and Light Proof system side-end caps. Degree of protection IP40 or IP43, according to the way that it is installed.

Technical Sheet





code MO004.3000

Series of semi-recessed, ceiling-mounted or suspended fixtures for direct diffused lighting. For linear LED sources or T16 fluorescent seamless lamps. 230/240V 50/60Hz integrated electronic supply. Available both as default modules and as modules to be assembled in a system. Body in extruded aluminium, painted or anodized finish. Opal white polycarbonate diffuser and Light Proof system side-end caps. Degree of protection IP40 or IP43, according to the way that it is installed.

Technical Sheet



code MO004.misura

Series of semi-recessed, ceiling-mounted or suspended fixtures for direct diffused lighting. For linear LED sources or T16 fluorescent seamless lamps. 230/240V 50/60Hz integrated electronic supply. Available both as default modules and as modules to be assembled in a system. Body in extruded aluminium, painted or anodized finish. Opal white polycarbonate diffuser and Light Proof system side-end caps. Degree of protection IP40 or IP43, according to the way that it is installed.

Technical Sheet



Angle connector couple wall/ceiling



code LTM211.90P

for wall/ceiling assembling

Technical Sheet



Fifty5 System Power cable kit with ceiling canopy



code LTM048.3/01

l.2000 mm

Technical Sheet



code LTM048.4/01

l.2000 mm

Technical Sheet



code LTM048.5/01

l.2000 mm

Technical Sheet



code LTM048.7/01

l.2000 mm

Technical Sheet





code LTM048.9/01

l.2000 mm

Technical Sheet



Fifty5 System Steel suspension kit



code LTM047.4000

single steel suspension kit l.2000mm. one every 1,5 mt, 2 pieces minimum

Technical Sheet



code LTM047

single steel suspension kit l.2000mm. one every 1,5 mt, 2 pieces minimum

Technical Sheet

