

Twenty 7 fixed round frame 10 - low conical cover

D



500















code TW210.930W/01







PRODUCT DESCRIPTION

Recessed projectors with round ceiling frame for integrated LED Chip On Board spot light, low luminance. Recessed ceiling lamp body and painted aluminum optical group. 99.99% pure aluminium metallized reflector. Possibility to mount satin, Fresnel and microprismatic lenses (UGR<19) in polycarbonate. Anti-glare honeycomb grid in painted aluminum. Degree of protection IP20.

PRODUCT SPECS

Installation method	Recessed with frame
Light source	LED
Absorbed power	17 W / 24,3 W
Color temperature	3000K
Color rendering index CRI	>90
Optic	Wide 41°
Finishing	White
Luminous flux of the product	1963 lm / 2793 lm
Luminous efficiency	115 lm/W
MacAdam color tolerance	3
Life time estimate	3SDCM 50000h L90 B10 ta 25°C
Energy efficiency class	D/E
Dimension	H130 Ø131 mm
Hole size	Ø 154 mm
IP Grade	IP20
Protection Class	Class III appliance
Product Spec	Circular shape
Power supply/Transformer	Not included
Protocol	See power supply

WEB PAGE








Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.


Accessori Lens ø 105 Asymmetric microprismatic 15° lens Ø 105



code L105A uncategorized

Technical Sheet


Accessori Lens ø 105 Ellipsoidal lens Ø 105



code L105E uncategorized



Accessori Lens ø 105 Honey comb louver Ø 105



code L105R uncategorized



Accessori Lens ø 105 Satin lens Ø 105



code L105S uncategorized

