



## Leva System Tilt version B3

code LV091K.930S/01



















#### PRODUCT DESCRIPTION

Trimless, fully-retracting flush recessed modular systems for housing system profiles and MINIFILE, FILE, FILE 2, FILE 2 COMPLEMENTI, LEVA and FARETÈN finished modules for creating cuts of continuous light or where light modules alternate to voids, in plaster-board false-ceiling or false-walls or in concrete or brick walls. Painted or anodised extruded aluminium body, with a predefined length or cut to size. To be completed with side end caps and finishing cover for the empty spaces in a retracted position to determine an effect of solids and voids. Can also be used with LED linear light sources, to be completed with opal white PC diffusing screen and remote power supplies, to create retracted grooves of light.

#### **PRODUCT SPECS**

Light source Absorbed power 3x2,2 W Color temperature 3000K Color rendering index CRI Optic Spot 20° Finishing White box - black optic Luminous flux of the product Luminous efficiency 99 lm/W MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Protocol On/Off Energy efficiency class E	Installation method	system
Color temperature 3000K  Color rendering index CRI >90  Optic Spot 20°  Finishing White box - black optic  Luminous flux of the product 651 lm  Luminous efficiency 99 lm/W  MacAdam color tolerance 2  Life time estimate 50000h Ta 25° L90B10  Protocol On/Off	Light source	LED
Color rendering index CRI >90  Optic Spot 20°  Finishing White box - black optic  Luminous flux of the product 651 lm  Luminous efficiency 99 lm/W  MacAdam color tolerance 2  Life time estimate 50000h Ta 25° L90B10  Protocol On/Off	Absorbed power	3x2,2 W
Optic Spot 20° Finishing White box - black optic Luminous flux of the product 651 Im Luminous efficiency 99 Im/W MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Protocol On/Off	Color temperature	3000K
Finishing White box - black optic Luminous flux of the product 651 lm Luminous efficiency 99 lm/W MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Protocol On/Off	Color rendering index CRI	>90
Luminous flux of the product 651 lm  Luminous efficiency 99 lm/W  MacAdam color tolerance 2  Life time estimate 50000h Ta 25° L90B10  Protocol On/Off	Optic	Spot 20°
Luminous efficiency99 lm/WMacAdam color tolerance2Life time estimate50000h Ta 25° L90B10ProtocolOn/Off	Finishing	White box - black optic
MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Protocol On/Off	Luminous flux of the product	651 lm
Life time estimate 50000h Ta 25° L90B10 Protocol On/Off	Luminous efficiency	99 lm/W
Protocol On/Off	MacAdam color tolerance	2
	Life time estimate	50000h Ta 25° L90B10
Energy efficiency class E	Protocol	On/Off
	Energy efficiency class	E
Weight 1.23 Kg	Weight	1.23 Kg
Dimension L100xW75xH110+38 mm	Dimension	L100xW75xH110+38 mm
IP Grade IP20	IP Grade	IP20
Power supply 220-240V 50-60Hz	Power supply	220-240V 50-60Hz

**WEB PAGE** 



**ASSEMBLY** 



### MANDATORY ACCESSORY ACCORDING TO THE TYPE OF INSTALLATION

# **Box Leva 3 trimless tilting**



code LV003B/01

Trimless recessed uncategorized wallbox for brick wall / wallbox for false ceiling. Bianco finishing wallbox for brick wall / wallbox for false ceiling

