

IFerrosi spot 120

code IF20.940W/44C



500

700
















350 350 25 25 274



PRODUCT DESCRIPTION

Family of outdoor floor or wall luminaires, available in finished modules or in a modular system for maximum customization. Versions with LED source projectors for accent light are available. Poles of different heights from 700mm to 3000mm are available, to be combined with spots of 6.7W or 18W. Fixing base or possibility to install in different surfaces: flange for wooden surfaces, clamp for concrete and stake for ground. IP54.

PRODUCT SPECS

Light source Absorbed power 18 W Color temperature 4000K Color rendering index CRI Optic Wide 39° Finishing Champagne gold	d
Color temperature 4000K Color rendering index CRI >90 Optic Wide 39°	
Color rendering index CRI >90 Optic Wide 39°	
Optic Wide 39°	
- P	
Finishing Champagne gold	
1 0 0	
Luminous flux of the product 1694 lm	
Luminous efficiency 94 lm/W	
Life time estimate 50000h L90 B10 Ta 2	25°C
Protocol On/Off	
Energy efficiency class D	
Weight 1.3 Kg	
Dimension L174xH75 Ø120 mm	
IP Grade Ip66 / Ip66	
Protection Class	
Product Spec Circular shape	
Power supply/Transformer Not included	
Protocol See power supply	

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

MANDATORY ACCESSORIES

AE500.20C1



code AE500.20C1

Electronic power supply current

